



RESISTANCE VALUES AT INTERMEDIATE TEMPERATURES				
T <sub>OPER</sub> (°C)	R <sub>T</sub> /R <sub>25</sub>	ΔT (K)	TCR (%/K)	R <sub>25</sub> -VALUE (5k Ω)
- 40	33.21	0.68	6.57	166.1
- 35	23.99	0.66	6.36	120.0
- 30	17.52	0.64	6.15	87.60
- 25	12.93	0.62	5.95	64.65
- 20	9.636	0.59	5.76	48.18
- 15	7.250	0.57	5.58	36.25
- 10	5.505	0.55	5.40	27.52
- 5	4.216	0.52	5.24	21.08
0	3.255	0.50	5.08	16.28
5	2.534	0.50	4.92	12.67
10	1.987	0.50	4.78	9.936
15	1.570	0.50	4.64	7.849
20	1.249	0.50	4.50	6.244
25	1.000	0.50	4.37	5.000
30	0.8059	0.50	4.25	4.030
35	0.6535	0.50	4.13	3.267
40	0.5330	0.50	4.02	2.665
45	0.4372	0.50	3.91	2.186
50	0.3605	0.50	3.80	1.803
55	0.2989	0.55	3.70	1.494
60	0.2490	0.61	3.60	1.245
65	0.2084	0.66	3.51	1.042
70	0.1753	0.72	3.42	0.8765
75	0.1481	0.77	3.33	0.7405
80	0.1256	0.83	3.25	0.6282
85	0.1070	0.89	3.16	0.5355
90	0.09154	0.95	3.09	0.4577
95	0.07860	1.02	3.01	0.3930
100	0.06773	1.08	2.94	0.3387
105	0.05858	1.14	2.87	0.2929
110	0.05083	1.21	2.80	0.2542
115	0.04426	1.27	2.73	0.2213
120	0.03866	1.34	2.67	0.1933
125	0.03387	1.41	2.61	0.1694